

Suntech STP275-20/Wfw 275Wp . Das Suntech STP275-20/ Wfw ist ein polykristallines Solarmodul mit 275Wp. * neuer und unbenutzter Restposten * Module können leichte Lagerspuren aufweisen * Ersatzmodul für bestehende Anlagen zur Schadensregulierung bei Versicherungsällen!

0 5 10 15 20 25 30 35 40 STP275 - 20/Wfm ????? 1000 ?????????????????????????????????
??-?????-????(STP275-20/Wfm) ??? ???? ??? 6??? ?????? 60?(6×10) ???? ...

STP275 - 20/Wfw Strom-Spannungs- & Leistungs- Spannungskennlinie (285) Mechanische Eigenschaften
Solarzelle Polykristallines Silizium 6 Zoll Anzahl der Zellen 60 (6 x10) Abmessungen 1.650 × 992
× 35 mm (64,96 x 39,1 x 1,4 Zoll) Gewicht 18,3 kg Frontglas 3,2 mm (0,13 Zoll) gehärtes Glas

NOCT: Irradiance 800 W/m2, ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class
AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP280- 20/Wfw
STP275 - 20/Wfw STP270 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature
(NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 ...

Wuxi Suntech Power Co., Ltd. STP275-285 - 20 /Wfw-TG
????????????????????????????(????????????PDF????????????????)

Suntech STP275 - 20/Wfw Home; Suntech STP275 - 20/Wfw 275 Watt POLYCRYSTALLINE SOLAR
MODULE. ?????? ???? : 1 - ???? ???? ???? (????? ???? ???? ???? ???? Tier 1 ????? ???? ????) ???? ???? ????
?????? ???? ???? ?? ??? ??? ...

STP275 - 20/Wfw Superpoly. 0 50 100 150 200 250 300 0 2 4 6 8 10 12 0 10 20 30 40 Current (A) Power (W)
Votage(V) NMOT STP285-20/ Wfw STP280-20/ Wfw STP275-20/ Wfw Maximum Power at NMOT (Pmax)
214.4 W 210.3 W 206.4 W Optimum Operating Voltage (Vmp) 39.8 V 39.5 V 39.2 V Optimum Operating
Current (Imp) 7.20 A 7.14 A 7.07 A

STP 275 - 20 / Wfw Suntech STP 275-20 / Wfv Projektowanie i montaz systemów fotowoltaicznych,
dystribucja komponentów Montá?e s.r.o. ... STP275 - 20/Wfw, STP270 - 20/Wfw, STP265 -
20/Wfw. Dane mog? ulec zmianie! Adres siedziby firmy:, U panelarny 10, 772 00 O?omuniec, Republika
Czeska

NOCT: Irradiance 800 W/m2, ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class
AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw
STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature
(NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 ...

Stp275 20 wfw Slovenia

STP275-285 - 20 /Wfw-TG Wuxi Suntech Power Co., Ltd. Technology: Power Range: Wp Region: China
Contact Manufacturer Product is no longer manufactured. Solar Panel MY Solar - M10 Series
MY-M10/144-540-560W From EUR0.0616 / Wp ...

STP275 - 20/Wfw 5 PREMIUM Years WARRANTY Weak light Excellent weak light performance More
power output in weak light condition, such as haze, cloudy, and morning lower hot spots Reduce the hot spots
and minimize panel degradation ** Certifications and standards: IEC 61215, IEC 61730, conformity to CE

Painel solar fotovoltaico de 60 células, de excelente qualidade, policristalino, com uma potência
de 275 Wp, com 5 busbar, de um dos fabricantes mais reconhecidos mundialmente pela sua qualidade,
inovação e fiabilidade. Tolerância positiva. Com estas características, proporciona a
melhor relação preço/prestação em instalações de autoconsumo
fotovoltaico.

STP280 - 20/Wfw STP275 - 20/Wfw STP270 - 20/Wfw 0/+5W Positive tolerance Positive tolerance of up to
5 W delivers higher output reliability IP68 Rated Junction Box The Suntech IP68 rated junction box ensures an
outstanding waterproof level, supports installations in all orientations and

Maximum Series Fuse Rating 20 A Power Tolerance 0/+5 W STC: Irradiance 1000 W/m², module
temperature 25 °C, AM=1.5; Best in Class AAA solar simulator (IEC 60904-9) used, power
measurement uncertainty is within +/- 3% NOCT STP285S-20/ Wfw STP280S-20/ Wfw STP275S-20/ Wfw
Maximum Power at NOCT (P_{max}) 210.4 W 206.5 W 202.8 W

Wuxi Suntech Power Co., Ltd. Solar Panel Series STP265-275 - 20/Wfw. Detailed profile including pictures,
certification details and manufacturer PDF ... STP270-20/ Wfw STP275-20/ Wfw Warranty Product Warranty
12 Years Power Warranty 25 Years of 80.7% Output Power Electrical Data at STC Maximum Power (P_{max})
265 Wp 270 Wp

?STP275-20/Wfw? <?????????> ??????????2??(????????325W????????275W)????

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class
AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw
STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature
(NOCT) 45±177;2±176;C Temperature Coefficient of P_{max} -0.41 %/°C

Web: <https://borrellipneumatica.eu>

