



Stp275 20 wfw Uganda

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% STP275- 20/Wfw STP270 - 20/Wfw STP265 - 20/Wfw Temperature Characteristics Nominal Operating Cell Temperature (NOCT) 45±2°C Temperature Coefficient of Pmax -0.41 %/°C

STP 275 - 20 / Wfw Suntech STP 275-20 / Wfw Projektowanie i montaż systemów fotowoltaicznych, dystrybucja komponentów Montaż s.r.o. ... STP275 - 20/Wfw, STP270 - 20/Wfw, STP265 - 20/Wfw. Dane mogą ulec zmianie! Adres siedziby firmy:, U panelarny 10, 772 00 Olomouc, Republika Czeska

STP275 - 20/Wfw Superpoly. 0 50 100 150 200 250 300 0 2 4 6 8 10 12 0 10 20 30 40 Current (A) Power (W) Voltage(V) NMOT STP285-20/ Wfw STP280-20/ Wfw STP275-20/ Wfw Maximum Power at NMOT (Pmax) 214.4 W 210.3 W 206.4 W Optimum Operating Voltage (Vmp) 39.8 V 39.5 V 39.2 V Optimum Operating Current (Imp) 7.20 A 7.14 A 7.07 A

Suntech STP275-20/Wfw 275Wp . Das Suntech STP275-20/ Wfw ist ein polykristallines Solarmodul mit 275Wp. * neuer und unbenutzter Restposten * Module können leichte Lagerspuren aufweisen * Ersatzmodul für bestehende Anlagen zur Schadensregulierung bei Versicherungsfällen!

Suntech STP275 - 20/Wfw Home; Suntech STP275 - 20/Wfw 275 Watt POLYCRYSTALLINE SOLAR MODULE. ?????? : 1 - ?????? (????? ???? ???? ???? ???? Tier 1 ?????? ???? ????) ?????? ???? ???? ???? ???? ???? ???? ???? ???? ...

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3% All technical data at standard test condition

Maximum Series Fuse Rating 20 A Power Tolerance 0/+5 W STC: Irradiance 1000 W/m², module temperature 25 °C, AM=1.5; Tolerances of Pmax, Voc and Isc are all within ±5% NMOT STP285-20/ Wfm STP280-20/ Wfm STP275-20/ Wfm Maximum Power at NMOT (Pmax) 214.4 W 210.3 W 206.4 W Optimum Operating Voltage (Vmp) 29.8 V 29.5 V 29.2 V

?????40????????????????????????????????????160????????????????????????????????????

STP275-285 - 20 /Wfw-TG Wuxi Suntech Power Co., Ltd. Technology: Power Range: Wp Region: China Contact Manufacturer Product is no longer manufactured. Solar Panel MY Solar - M10 Series MY-M10/144-540-560W From EUR0.0616 / Wp ...

Stp275 20 wfw Uganda

Wuxi Suntech Power Co., Ltd. Solar Panel Series STP265-275 - 20/Wfw. Detailed profile including pictures, certification details and manufacturer PDF ... STP270-20/ Wfw STP275-20/ Wfw Warranty Product Warranty 12 Years Power Warranty 25 Years of 80.7% Output Power Electrical Data at STC Maximum Power (Pmax) 265 Wp 270 Wp

Current-Voltage & Power-Voltage Curve (275-20) Excellent performance under weak light conditions: at an irradiation intensity of 200 W/m² (AM 1.5, 25 °C), 96.5% or higher of the STC efficiency (1000 W/m²) is achieved Dealer information Mechanical Characteristics Solar Cell ...

Painel solar fotovoltaico de 60 células, de excelente qualidade, policristalino, com uma potência de 275 Wp, com 5 busbar, de um dos fabricantes mais reconhecidos mundialmente pela sua qualidade, inovação e fiabilidade. Tolerância positiva. Com estas características, proporciona a melhor relação preço/performance em instalações de autoconsumo fotovoltaico.

```
0 5 10 15 20 25 30 35 40 STP275 - 20/Wfm ????? 1000 ?????????????????????????????????
??-?????-????(STP275-20/Wfm) ??? ???? ??? 6??? ?????? 60?(6&#215;10) ???? ...
```

STP280 - 20/Wfw STP275 - 20/Wfw STP270 - 20/Wfw 0/+5W Positive tolerance Positive tolerance of up to 5 W delivers higher output reliability IP68 Rated Junction Box The Suntech IP68 rated junction box ensures an outstanding waterproof level, supports installations in all orientations and

?? 20??? 40??? ?/? 30 ?/? 6 28 ?/? 180 840 ??? ???? (NOCT) 45±2°C ??? (Pmax)???
-0.41 %/°C ??? (Voc)??? -0.33 %/°C ??? (Isc)??? 0.067 %/°C ??? STC STP275-20/
Wfw STP270-20/ Wfw STP265 ...

Wuxi Suntech Power Co., Ltd. STP275-285 - 20 /WfW-TG
 ?????????????????????(????????????PDF????????????????

STP275 - 20/Wfw Strom-Spannungs- & Leistungs- Spannungskennlinie (285) Mechanische Eigenschaften
Solarzelle Polykristallines Silizium 6 Zoll Anzahl der Zellen 60 (6 x10) Abmessungen 1.650 × 992
× 35 mm (64,96 x 39,1 x 1,4 Zoll) Gewicht 18,3 kg Frontglas 3,2 mm (0,13 Zoll) gehärtes Glas

Web: <https://borrellipneumatica.eu>

